

Built for Contractors - Built to Last

HIGHEST QUALITY - Steel and Aluminum construction. No plastic shrouds or off shore compressors

ELECTRICALLY FRIENDLY - Won't blow 15A Circuits, Extension Cords can be used as needed

PERMA LUBE - Oil-Less Design for maintenance free operation and quick cold weather starts

INCLINE DESIGN - Offers stable multi-angle worksite compatibility for all construction jobs



SPECIFICATIONS	<u>T-617HDN</u>	<u>T-30HP</u>	<u>T-2820ST</u>	<u>T-200ST</u>
Air Displacement	1.8CFM	4.8 CFM	9.0 CFM	8.0 CFM
Air Delivery	.90 CFM @100 PSI	2.75 CFM @ 100 PSI	5.0 CFM @ 100 PSI	4.6 CFM @ 100 PSI
Pressure Switch	On 100 PSI - Off 125 PSI	On 100 PSI - Off 125 PSI	On 100 PSI - Off 125 PSI	On 110 PSI - Off 135 PSI
Motor	1/2 HP Electric	1-1/4 HP Electric	2 HP Electric	2 HP Electric
Tank Capacity	2 Gallon Hotdog	4.5 Gallon Pancake	4 Gallon Twin Stack	4 Gallon Twin Stack
Weight	26 lbs.	53 lbs.	66 lbs.	72 lbs.
Dimensions LxWxH (in)	16.5 x 8 x 16.8	16 x 16 x 19.8	20 x 15.6 x 16.5	19 x 14.6 x 16.3
Low Amp Draw	4.2A	12.0A	13.5A	13.0A
Recovery Time	38 Seconds	18 seconds	9 seconds	12 seconds
Regulator & Gauge	--	--	Supplied	Supplied
RPM	1700	1700	1700	1725
Decibel Rating	60 dB	74 dB	74 dB	75 dB
Finish Guns	1-2	3-4	5+	5-6
Framing Guns	--	1-2	3+	3-4
Roofing Guns	--	1-2	3+	3-4

PROUDLY MANUFACTURED IN THE USA